



EXELLO Diesel Engine Oil 15W-40

Product Description

Exello is a multi-grade high performance diesel engine oil designed to operate under extreme conditions and heavy loads. It has the US patented oil and metal treatment technology that provides the engine excellent shield against wear caused by friction, heat, corrosion, abrasion and impact, while at the same time boosting performance efficiency.

Applications

For lubrication in all four-stroke diesel engines, heavy duty diesel, road transport, barges, and construction industry units.

Benefits

- Formulated with Pertua's Durasyn Technology
- Can withstand operation under extreme conditions and heavy loads
- Provides excellent engine cleanliness in all service conditions
- Superior oxidation and thermal stability
- Protection from cold start ups
- Suited for extended drain intervals
- Increases fuel economy

Typical Properties

Properties	Method	Unit	Typical Result
Density at 15°C, Relative	ASTM D4052	g/mL	0.870
Viscosity, Kinematic 100°C	ASTM D445	centistokes	15.28
Viscosity, Kinematic 40°C	ASTM D445	centistokes	153.2
Viscosity Index	ASTM D2270		100
Pour Point	ASTM D97-12	Degree Celsius	-18
Flash Point, PMCC	ASTM D92-12a	Degree Celsius	260
Total Base Number	ASTM D2896-11	mgKOH/g	5.1

Performance Claims

API CJ-4

ACEA A3/B4

Recommendations for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

Health and Safety

This product does not pose a health or safety hazard when used in the recommended application and when proper industrial safety practices are observed. As with all industrial oils and lubricants, prolonged contact with skin should be avoided, especially with used oils. Wash skin with soap and water after contact. Take used oil to an authorized government accredited recycler.

PERTUA is a trademark of PRIMETECH OIL INC. Typical properties are typical of those obtained in normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information herein is subject to change without notice. For more information, visit www.pertua.com