



# APEX PCO Gasoline Engine Oil 15W-50

## Product Description

Apex PCO is an advance formulation gasoline engine oil with unparalleled anti-friction protection that prevents metal-to-metal contact even under extreme engine operating conditions and high speeds.

## Applications

- Fully formulated gas engine oil for gasoline and CNG/LPG fueled spark ignition engines where conventional API SN passenger car motor oils are recommended.
- For naturally aspirated and turbocharged petrol engines in passenger cars.
- For diesel engines in passenger car and light commercials requiring API CF/SN classification.

## Benefits

- Provides additional horsepower and torque
- Restores Engine efficiency
- Provides excellent engine cleanliness in all service conditions
- Protects the engine from cold start-ups
- Safe and suitable for all types of Gasoline engine

## Typical Properties

Properties	Method	Unit	Typical Result
Density at 15°C, Relative	ASTM D4052	g/mL	0.868
Viscosity, Kinematic 100°C	ASTM D445	centistokes	16.57
Viscosity, Kinematic 40°C	ASTM D445	centistokes	151.9
Viscosity Index	ASTM D2270		116
Pour Point	ASTM D97-12	Degree Celsius	-18
Flash Point, PMCC	ASTM D92-12a	Degree Celsius	260
Total Base Number	ASTM D2896-11	mg KOH/g	1.6

## Performance Claims

API SN

ACEA A3/B4

## Recommendation for Use

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

## Health and Safety

This product does not pose a health or safety hazard when used in the recommended application and when proper industrial safety practices are observed. As with all industrial oils and lubricants, prolonged contact with skin should be avoided, especially with used oils. Wash skin with soap and water after contact. Take used oil to an authorized government accredited recycler

*PERTUA is a trademark of PRIMETECH OIL INC. Typical properties are typical of those obtained in normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information herein is subject to change without notice. For more information, visit [www.pertua.com](http://www.pertua.com)*